


eurobi 2C⁺

EPOXY-POLYURETHANE BI-COMPONENT ADHESIVE



Bicomponent epoxy-polyurethane adhesive completely **odorless water-free and solvent-free**, suitable for laying traditional or prefinished wooden floors on any kind of surfaces, also pre-existent and nonabsorbent ones (ceramic, marble, etc.). Eurobi 2C⁺ Solvent Free guarantees high workability, elasticity and a long time of use. Suitable on underfloor heating systems. The absence of solvents and the very low concentration of other substances volatile organic ensures greater safety for the user and compliance with environmental quality.

SOLVENT FREE

ÉMISSIONS DANS L'AIR INTÉRIEUR



A+

A+ A B C

Chemical-Physical characteristics (20°C - 60% R.H.)

Component A appearance	Thick paste	Specific gravity of mix (UNI EN 542)	1,699 g/cm ³
Component B appearance	Liquid paste	Concentration of solvents	Zero VOC
Mixture viscosity (Brookfield rev.nr.7 50 rpm)	49000 mPa		

Mixing ratios and Times (20°C - 60% R.H.)

Mixing ratio A + B	90 + 10 in weight	Set to traffic	24 h
Pot life	2 h	Polishing	2 - 3 days
Adjustment time	8 - 10 h	Possible dilution	Max 100 ml P.E.P.P. promoter

Technical characteristics (20°C - 60% R.H.)

Consumption (10 mm notched trowel)	900 - 1400 gr/m ²	Application temp.	> 10°C < 35°C
Shear strenght (Rif. EN 14293)	> 3,5 N/mm ²		
ADHESIVE COMPLIANT UNI EN 14293			

Storage & Labeling

Storage in original packaging sealed at T > 10 °C	12 months	Symbols of danger	Comp. A: Xi Comp. B: Xi
Packaging	Buckets 9 Kg + 1 Kg		



10kg e

9 kg (A) + 1 kg (B)



europosca⁺
ULTRABOND ADHESIVE

Eurolegno distribution inc.
US and Canada distribution
5349 Ferrier
Montreal, Quebec
Canada, H4P 1M1
Tel: # 001 - 514 - 739 - 9416
info@eurolegnoluxuryfloors.com